

REPORT DOCUMENTATION PAGE		Form Approved OMB NO. 0704-0188	
Public Reporting Burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington DC 20503			
1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE: 31-Aug-2007	3. REPORT TYPE AND DATES COVERED Final Report 1-Jun-2003 - 31-May-2007
4. TITLE AND SUBTITLE Polycarbosilane Elastomers via Chain-Internal and Chain-End Latent Crosslinking		5. FUNDING NUMBERS DAAD19-03-1-0083	
6. AUTHORS Kenneth Wagener, Hector Zuluaga, Paula Delgado		8. PERFORMING ORGANIZATION REPORT NUMBER	
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES University of Florida - Gainesville Division of Sponsored Research 219 Grinter Hall Gainesville, FL 32611 -5500			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211		10. SPONSORING / MONITORING AGENCY REPORT NUMBER 44559-CH.1	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not contrued as an official Department of the Army position, policy or decision, unless so designated by other documentation.			
12. DISTRIBUTION AVAILABILITY STATEMENT Distribution authorized to U.S. Government Agencies Only, Contains Proprieta		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The abstract is below since many authors do not follow the 200 word limit			
14. SUBJECT TERMS elastomers, durable, solvent resistant, hybrid silicon materials, polycarbosilane, polycarbosilane materials		15. NUMBER OF PAGES Unknown due to possible attachments	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

Report Title

Polycarbosilane Elastomers via Chain-Internal and Chain-End Latent Crosslinking

ABSTRACT

The mission/objective of this work has been to identify a new class of hybrid polymers based on carbosilane/carbosiloxane chemistry, the objective being to create elastomers having excellent solvent resistance, high initial modulus, elasticity greater than 600%, and tensile strengths 2X greater than existing elastomers. Polymers have been synthesized and are being examined for their performance. All the required parameters for performance have been met excepting the tensile strength goal of 2X existing elastomers. While the project is now concluded from a funding perspective, we continue to examine the concept of dual latent crosslinking to achieve the tensile strength goal.

List of papers submitted or published that acknowledge ARO support during this reporting period. List the papers, including journal references, in the following categories:

(a) Papers published in peer-reviewed journals (N/A for none)

Two manuscripts are in preparation to describe the latest work being done here (work completed by Dr. Piotr Matloka and Ms. Paula Delgado). These papers will be submitted by the end of the year.

Number of Papers published in peer-reviewed journals: 0.00

(b) Papers published in non-peer-reviewed journals or in conference proceedings (N/A for none)

Number of Papers published in non peer-reviewed journals: 0.00

(c) Presentations

The research completed during the past 6 months will be presented once we have the final answer regarding the dual latent crosslinking concept fully examined. I will be using alternate funds (the Butler Endowment Funds) to continue to gather these data. The goal is to illustrate that hydrolytic internal latent crosslinking, followed by thermal, ring opening latent crosslinking, leads to significant enhancements in tenacity.

Number of Presentations: 0.00

Non Peer-Reviewed Conference Proceeding publications (other than abstracts):

This research likely will be presented at the 2008 NATO sponsored metathesis materials conference to be held in Rumania. I have tentatively sent this title to them for consideration.

Number of Non Peer-Reviewed Conference Proceeding publications (other than abstracts): 0

Peer-Reviewed Conference Proceeding publications (other than abstracts):

Number of Peer-Reviewed Conference Proceeding publications (other than abstracts): 0

(d) Manuscripts

Number of Manuscripts: 0.00

Number of Inventions:

Graduate Students

<u>NAME</u>	<u>PERCENT SUPPORTED</u>
Paula Delgado	0.50
Piotr Matkola	0.10
FTE Equivalent:	0.60
Total Number:	2

Names of Post Doctorates

<u>NAME</u>	<u>PERCENT SUPPORTED</u>
Fabio Zuluaga	0.10
FTE Equivalent:	0.10
Total Number:	1

Names of Faculty Supported

<u>NAME</u>	<u>PERCENT SUPPORTED</u>	National Academy Member
K. B. Wagener	0.12	No
FTE Equivalent:	0.12	
Total Number:	1	

Names of Under Graduate students supported

<u>NAME</u>	<u>PERCENT SUPPORTED</u>
Zach Keane (now pursuing PhD at Bei	0.10
FTE Equivalent:	0.10
Total Number:	1

Student Metrics

This section only applies to graduating undergraduates supported by this agreement in this reporting period

The number of undergraduates funded by this agreement who graduated during this period: 1.00

The number of undergraduates funded by this agreement who graduated during this period with a degree in science, mathematics, engineering, or technology fields:..... 1.00

The number of undergraduates funded by your agreement who graduated during this period and will continue to pursue a graduate or Ph.D. degree in science, mathematics, engineering, or technology fields:..... 1.00

Number of graduating undergraduates who achieved a 3.5 GPA to 4.0 (4.0 max scale):..... 1.00

Number of graduating undergraduates funded by a DoD funded Center of Excellence grant for Education, Research and Engineering:..... 0.00

The number of undergraduates funded by your agreement who graduated during this period and intend to work for the Department of Defense 0.00

The number of undergraduates funded by your agreement who graduated during this period and will receive scholarships or fellowships for further studies in science, mathematics, engineering or technology fields:..... 1.00

Names of Personnel receiving masters degrees

NAME

Total Number:

Names of personnel receiving PHDs

NAME

Piotr Matkola

Total Number:

1

Names of other research staff

<u>NAME</u>	<u>PERCENT_SUPPORTED</u>
FTE Equivalent:	
Total Number:	

Sub Contractors (DD882)

Inventions (DD882)

5 Elastomeric Polymers

Patent Filed in US? (5d-1) Y

Patent Filed in Foreign Countries? (5d-2) N

Was the assignment forwarded to the contracting officer? (5e) Y

Foreign Countries of application (5g-2):

5a: Kenneth B. Wagener

5f-1a: University of Florida

5f-c: PO Box 117200

Gainesville FL 32611

5a: John C. Sworen

5f-1a: University of Florida

5f-c: PO Box 117200

Gainesville FL 32611

5a: Hector Fabio Zuluaga

5f-1a: University of Florida

5f-c: PO Box 117200

Gainesville FL 32611


5a: Piotr

5f-1a: Matloka

5f-c: University of Florida

Gainesville FL 32611

K. B. Wagener
George & Josephine Butler Polymer
Research Laboratory
Department of Chemistry, University of Florida
Gainesville, FL 32611 USA
Wagener@chem.ufl.edu



Objective: The mission of our ARO supported research has been to identify new silicon/hybrid elastomer materials for use under highly demanding conditions.

Silicon-based elastomers offer advantages over pure hydrocarbon materials (greater elongation, better low temperature performance, higher operating temperatures, better weathering performance), yet carbon based materials predominate on the basis of greater tensile strength (2X that of silicones). A superior elastomer will merge these performance parameters via the creation of hybrid silicon/carbon-based materials.

What We Have Done. We have introduced the concept of latent crosslinking to meet this objective. Linear carbosilane/carbosiloxane polymers are prepared first (to achieve the desired object shape), followed by latent crosslinking both internally and at chain-ends to fix the article's shape and achieve maximum materials performance. Proof-of-principle research has been completed via fundamental structure/behavior investigations.

Two of our materials properties objectives have been met. We see a 3X increase in modulus, coupled with a 2.5X increase in elongation for these hybrid materials in comparison with commercial silicones. Tenacities are the same as commercial materials, values less than needed to meet our stated objective.

We note that ***these tenacities are less than 0.1% of the theoretical maximum possible*** for such polymers, based on bond dissociation energy analysis. Obviously the problem is not the strength of the polymer chain, but rather the interaction between polymer chains.

We attribute the less-than-desired tenacity performance to insufficient latent crosslinking. Apparently, the moisture driven latent crosslinking chemistry implemented here is not complete – moisture doesn't fully penetrate the hydrophobic silicon hybrid polymer to induce sufficient crosslinking.

What We Have Done. The answer lies in chain-end latent crosslinking of a different nature, chemistry not driven by moisture.

We are implementing a dual-latent reaction concept to attack this tenacity challenge, using adduct forming chain-end latent crosslinks. The chain-end latent crosslinking reaction will be driven thermally, assuring complete conversion.


Two potential chain-end latent cross linkers are illustrated at the top of this report. The cyclocarbosilane structure is particularly relevant to this research, since they form adducts when opened (no small molecule released) and generate dimethyl silicon carbide structures.

Simply invoking thermally driven crosslinking is not enough. Dual latent crosslinking is necessary. Otherwise, the strategic advantage we offer (being able to shape the desired object before crosslinking) would be lost; the linear polymer would soften and flow upon

exposure to heat before crosslinking took hold. Dual latent crosslinking is the key.

The existing moisture driven chain-internal chemistry first fixes the desired shape (so heat won't flow the polymer), then then a temperature ramp drives the thermal chain-end chemistry to crosslink the dangling chain ends. This chemistry is fully elucidated in the scheme below.

This dual latent crosslinking concept is fundamental in scope and is being investigated now. Should it prove beneficial, then we will expand the work towards investigation of silica-based fillers to achieve desired results.



Progress to End of Funding Period

A number of monomers have been prepared that possess the necessary moisture driven chain-internal and thermally driven chain-end crosslink sites. The repeat units also contain oxyethylene or carbosilane repeat units as required for elasticity.

The unique end-group thermal crosslinker 1-methyl-1-undec-10-enyl-silacyclobutane remains stable as a potential crosslink during all of the chemistry that precedes it. It is available for the last thermally driven reaction for network formation (as shown in the reaction chemistry illustrated above).

While the formal ARO funding process for this work is now concluded, we intend to continue the work using private funds available to the Principal Investigator. These private funds are being provided by the Butler Endowment fund within the George & Josephine Butler Polymer Research Laboratory.

The final step of this work will be casting of films for curing at temperatures in excess of 180 °C . We will complete these curing studies and gather the necessary mechanical performance data to see if we can achieve our strength goal, which is to exceed the typical silicon based elastomer tenacity by a factor of at least 2.